



| REMARK:                             |  |                            | REV.          | REVISIONS REC.   | DATE:        |
|-------------------------------------|--|----------------------------|---------------|------------------|--------------|
| 1.                                  |  |                            | 1.            |                  |              |
| 2.                                  |  |                            | 2.            |                  |              |
| 3.                                  |  |                            | 3.            |                  |              |
| DRAWN BY                            |  | TOLERANCES                 | ANGLE:        | MODEL NAME:      |              |
| CHECKED BY                          |  | X. X $\pm 0.3$             | $\pm 1^\circ$ | ET-28-4S (COIL)  |              |
| APPROVED BY                         |  | X. XX $\pm 0.2$            | UNIT:         | BOBBIN MATERIAL: | UL REC.      |
|                                     |  | PIN PITCH: $\pm 0.2$       | MM            | PBT (WHITE)      | UL 94V-0     |
|                                     |  | WALL THICKNESS: $\pm 0.15$ | SCALE:        | PIN MATERIAL:    | REV.         |
|                                     |  |                            | 2:1           |                  | 0            |
| <b>Patron</b><br>Passive Elektronik |  |                            |               | DRAWING NO:      | DATE:        |
|                                     |  |                            |               | ET-2801-1        | 2010. 11. 30 |