



UNIT:mm

PART NO.	A	B	C	D	E	F	G	H	I	J	K
EB-16-001	18.0	15.0	5.0	13.0	10.0	8.0	16.0	20.0	19.0	10.0	6.0
EB-16-002	23.0	20.0	10.0	15.5	12.5	10.0	21.5	25.0	24.0	12.45	7.0
EB-16-003	27.0	22.5	12.5	18.0	15.0	13.0	24.1	30.0	28.5	15.4	10.0
EB-16-004	32.0	27.5	12.5	18.0	15.0	13.0	29.2	35.0	33.5	15.4	10.0
EB-16-005	35.0	30.0	15.0	23.0	20.0	17.0	33.0	37.0	35.0	19.4	13.0
EB-16-006	42.0	40.0	25.0	28.0	25.0	21.5	39.5	45.0	43.75	24.0	17.8

REMARK:			REV.	REVISIONS REC.		DATE:
1.			1.			
2.			2.			
3.			3.			
DRAWN BY		TOLERANCES	ANGLE:	MODEL NAME:		
CHECKED BY		X. X ±0.3 X. XX ±0.2 PIN PITCH: ±0.2 WALL THICKNESS: ±0.15	±1°	EB-16 SERIES CASE		
APPROVED BY			UNIT:	BOBBIN MATERIAL:		UL REC.
			MM	NYLON66;FR530		UL 94V-0
			SCALE:	PIN MATERIAL:		REV.
			2:1	CP WIRE		0
				DRAWING NO:		DATE:
				CASE-004		2010.11.28