

### III. Fast / Ultra Fast / Super Fast Recovery Rectifier

#### 3.0A Ultra Fast Recovery Rectifier HER301~HER308

(Package: DO-201AD)

<p><b>FEATURES</b></p> <ul style="list-style-type: none"> <li>• Plastic package carries Underwriters Laboratory Flammability Classification 94V-0</li> <li>• High speed switching for high efficiency</li> <li>• Low reverse leakage</li> <li>• High forward surge current capability</li> <li>• High temperature soldering guaranteed; 250 /10 seconds, 0.375" (9.5mm) lead length, 5 lbs. (2.3 kg) tension</li> </ul> <p><b>MECHANICAL DATA</b></p> <ul style="list-style-type: none"> <li>• Case : JEDEC DO-201AD, Molded plastic body</li> <li>• Terminals : Plated axial leads, solderable per MIL-STD-750, Method 2026</li> <li>• Polarity : Color band denoted cathode end</li> <li>• Mounting Position : Any</li> <li>• Weight : 0.04 ounce, 1.10 grams</li> </ul>	<p>Case: DO-201AD Dimensions in inches and (millimeters)</p>
--	--

#### Ratings & Electrical Characteristics

Characteristic	Symbol	HER 301	HER 302	HER 303	HER 304	HER 305	HER 306	HER 307	HER 308	Units
Maximum repetitive peak reverse voltage	$V_{RRM}$	50	100	200	300	400	600	800	1000	Volts
Maximum RMS voltage	$V_{RMS}$	35	70	140	210	280	420	560	700	Volts
Maximum DC blocking voltage	$V_{DC}$	50	100	200	300	400	600	800	1000	Volts
Maximum average forward rectified current 0.375" (9.5mm) lead length at $T_a = 50$	$I_o$	3.0								Amps
Peak forward surge current, 8.3ms single half sine-wave superimposed on rated load (JEDEC method)	$I_{FSM}$	100.0								Amps
Maximum instantaneous forward voltage at 3.0A	$V_F$	1.0		1.3		1.7				Volts
Maximum DC reverse current at rated DC blocking voltage	$I_R$			10.0		250.0				$\mu A$
Maximum reverse recovery time (Note 1)	$T_{rr}$			50		75				ns
Typical junction capacitance (Note 2)	$C_j$			70		50				PF
Typical thermal resistance (Note 3)	$R_{th-JA}$	20.0								/ W
Operating junction and storage temperature range	$T_j, T_{stg}$	-65 to +150								

Note :

1. Reverse recovery conditions:  $I_F = 0.5A$ ,  $I_R = 1.0A$ ,  $I_{RR} = 0.25A$
2. Measured at 1 MHz and applied reverse voltage of 4.0 volts DC
3. Thermal resistance from junction to ambient at 0.375" (9.5mm) lead length, P.C.B. mounted

<http://patron-components.com/>

# Ratings and Characteristic Curves of HER301~HER308

