

III. Fast / Ultra Fast / Super Fast Recovery Rectifier

2.0A Super Fast Recovery Rectifier SF21~SF28

(Package: DO-15)

<p>FEATURES</p> <ul style="list-style-type: none"> • The plastic package carries Underwriters Laboratory Flammability Classification 94V-0 • Super fast switching for high efficiency • Low reverse leakage • High forward surge current capability • High temperature soldering guaranteed: 250 /10 seconds, 0.375" (9.5mm) lead length, 5 lbs. (2.3 kg) tension <p>MECHANICAL DATA</p> <ul style="list-style-type: none"> • Case : JEDEC DO-15 molded plastic body • Terminals : Plated axial leads, solderable per MIL-STD-750, Method 2026 • Polarity : Color band denotes cathode end • Mounting Position : Any • Weight : 0.014 ounce, 0.40 grams 	<p>Case: DO-15 Dimensions in inches and (millimeters)</p>
---	---

Ratings & Electrical Characteristics

Ratings at 25 ambient temperature unless otherwise specified.

Single phase half-wave 60 Hz, resistive or inductive load, for capacitive load current derate by 20%.

Characteristic	Symbol	SF21	SF22	SF23	SF24	SF25	SF26	SF28	Units
Maximum repetitive peak reverse voltage	V_{RRM}	50	100	150	200	300	400	600	Volts
Maximum RMS voltage	V_{RMS}	35	70	105	140	210	280	420	Volts
Maximum DC blocking voltage	V_{DC}	50	100	150	200	300	400	600	Volts
Maximum average forward rectified current 0.375" (9.5mm) lead length at $T_a = 55$	I_o	2.0							Amps
Peak forward surge current, 8.3ms single half sine-wave superimposed on rated load (JEDEC method)	I_{FSM}	50.0							Amps
Maximum instantaneous forward voltage at 2.0A	V_F	0.95			1.30		1.70		Volts
Maximum DC reverse current $T_a = 25$ at rated DC blocking voltage $T_a = 100$	I_R	5.0 200.0							μA
Maximum reverse recovery time (Note 1)	T_{rr}	35							ns
Typical junction capacitance (Note 2)	C_j	60.0			30.0				pF
Typical thermal resistance (Note 3)	R_{th-JA}	50.0							/ W
Operating junction and storage temperature range	T_j, T_{stg}	-65 to +150							

Note :

1. Reverse recovery conditions: $I_F = 0.5A$, $I_R = 1.0A$, $I_{RR} = 0.25A$
2. Measured at 1 MHz and applied reverse voltage of 4.0 volts DC
3. Thermal resistance from junction to ambient at 0.375" (9.5mm) lead length, P.C.B. mounted

Ratings and Characteristic Curves of SF21~SF28




FIG. 2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG. 3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG. 4-TYPICAL REVERSE CHARACTERISTICS




FIG. 5-TYPICAL JUNCTION CAPACITANCE




FIG. 6-TYPICAL TRANSIENT THERMAL IMPEDANCE

